

# FONTAINE NO-SLACK®

## H7AWB

### Ideal for Severe Duty Applications

Extra heavy/Severe duty  
On/Off highway  
62,500 lbs vertical load  
150,000 lbs drawbar pull  
Approx top plate weight 315 lbs



### Mounting Bracket

#### Fontaine AWB Air Slide Bracket

- Fast, easy adjustments—great solution for customers who reposition the fifth wheel after every load
- Air cylinder drives a mechanical linkage to release the slide locking wedges
- Operates from closed position to protect the stainless steel shaft from corrosion, bending and roadspray
- Composite air cylinder features improved sealing performance and superior corrosion resistance for longer service life
- Available in a wide range of mounting heights and travel lengths to meet your hauling needs

### Top Plate

#### Fontaine No-Slack® H7 Series Extra Heavy Duty/Severe Duty Cast Steel

- **No-Slack lock self-adjusts to accommodate kingpin wear**
  - Switch from trailer to trailer hassle-free
  - Snug, secure connection
  - Reduces shock inputs into frame when braking/accelerating
  - Improves driver comfort
  - Reduces driver complaints
  - Extends service life of components
- **Locking trigger helps minimize high-hitching**
  - Reduces driver frustration
  - Reduces tractor, trailer and tire damage
  - The industries best defense against false coupling
  - Saves expensive wrecker and clean up bills
- **Easy coupling force—only 30 lbs!**
  - Less wear and tear on the kingpin
  - Extends service life of drivetrain components
- **Pull handle is the easiest to operate in the industry**
  - Opens easily with a simple, straight pull of the handle
  - No complicated opening sequence to remember




www.fifthwheel.com • 800-874-9780 • Email: parts@fifthwheel.com

\* See your Fontaine Representative for application details or refer to Application Guide (LT-076) on website

©2019 Fontaine Fifth Wheel • LT-250 • March 2019 R4

@FontaineFifthWheel 

@FifthWheelParts 

Get the app @ FifthWheel.com/app 