

Weight Saving Assemblies

Adjustable Plate Bracket No-Slack® II NT **APB** Stationary Standard duty



No-Slack® II NT
50,000 pounds vertical load

Part Number	Fifth Wheel Height	Weight
SLNTAPB6250	6-1/4"	309 lbs
SLNTAPB7250	7-1/4"	314 lbs
SLNTAPB8250	8-1/4"	319 lbs
SLNTAPB9250	9-1/4"	324 lbs

Typical left hand model shown in chart.

Options

- Right hand (replace **SL** with **SR**)
- Air actuated (replace **SL** with **AA**): add 5 lbs

Features

A fixed fifth wheel is economical and strong, but it limits your hauling options. Now you can get the strength and economy of a fixed fifth wheel with the flexibility of slide increments, thanks to the new APB adjustable plate mount bracket.

- Brackets are welded to a 3/8" steel plate with six bolt holes on each side for mounting versatility
- Two-inch mounting increments make it easy to adjust your load evenly

Stationary Bracket Mount No-Slack® II NT **SMB** Stationary Standard duty



No-Slack® II NT
50,000 pounds vertical load

Part Number	Fifth Wheel Height	Weight
SLNTSMB5875	5-7/8"	264 lbs
SLNTSMB6875	6-7/8"	269 lbs
SLNTSMB7875	7-7/8"	274 lbs

Typical left hand model shown in chart.

Options

- Right hand (replace **SL** with **SR**)
- Air actuated (replace **SL** with **AA**): add 5 lbs

Features

SMB fifth wheels are ideal for applications where axle weight, bridge length and kingpin settings remain constant. The SMB model is rapidly gaining in popularity. The mounting brackets are welded directly to the mounting base on your vehicle to save weight and cut costs.

