

FONTAINE NO-SLACK®



6000BSL

Weight savings fixed mount Fabricated plate

Standard/Moderate duty

On highway only

50,000 lbs vertical load

150,000 lbs drawbar pull

Approx top plate weight 205 lbs

Mounting Bracket

Fontaine BSL Weight Savings Fixed Mount Fabricated Bracket

- BSL fifth wheels are ideal for applications where axle weight, bridge length and kingpin settings remain constant
- BSL brackets are welded directly to the mounting base on your vehicle to save weight and cut costs
- Rapidly gaining in popularity due to weight savings, simplicity of design and overall economy

Top Plate

Fontaine No-Slack® 6000 Series Stamped Steel

- **No-Slack lock self-adjusts to accommodate kingpin wear**
 - Switch from trailer to trailer hassle-free
 - Snug, secure connection
 - Reduces shock inputs into frame when braking/accelerating
 - Improves driver comfort
 - Reduces driver complaints
 - Extends service life of components
- **Locking trigger helps minimize high-hitching**
 - Reduces driver frustration
 - Reduces tractor, trailer and tire damage
 - The industries best defence against false coupling
 - Saves expensive wrecker and clean up bills
- **Easy coupling force—only 30 lbs!**
 - Less wear and tear on the kingpin
 - Extends service life of drivetrain components
- **Pull handle is the easiest to operate in the industry**
 - Opens easily with a simple, straight pull of the handle
 - No complicated opening sequence to remember

Top Plate Performance Options

- **Air actuated**— In-cab air release valve located on the dash opens the fifth wheel lock only when the tractor parking brakes are set.



www.fifthwheel.com • 800-874-9780 • Email: parts@fifthwheel.com

